

i-SENSYS X 1800P Series

# HIGH-VOLUME, HIGH-SPEED PRINTERS WITH ROBUST SECURITY











# i-SENSYS X 1800P Series

# **VERSATILE PRINTING**

 Versatile Printing with up to six different optional paper tray and pedestal configurations, the i-SENSYS X 1800P can operate as a standard desk top, or become a large free standing work station. With a variety of supported media sizes, it can be tailored for any business

# **PROTECTION AGAINST THREATS**

• 360-degree security ensures complete document, device and network security. Security features include encrypted secure print, verify system at start-up, and network protection

# CONTROL AND MAINTENANCE

 Flexible user management solutions for business administrators and IT department. Remote access to the device control functions, along with the toner status tool reduces downtime

### (O) ACCELERATE EFFICIENCY

 Print large volumes of documents with optional additional paper cassettes to a maximum capacity of 4,300 sheets

## **QUICK FACTS**


### i-SENSYS X 1861P

- Print speed: 61ppm (A4)
- Print resolution: Up to 1200 x 1200 dpi
- · Automatic double-sided printing
- uniFLOW Online Express
- Network, USB and Wi-Fi connectivity
- · Standard paper input: 650-sheet

### i-SENSYS X 1871P

- Print speed: 71ppm (A4)
- Print resolution: Up to 1200 x 1200 dpi
- Automatic double-sided printing
- uniFLOW Online Express
- Network, USB and Wi-Fi connectivity
- · Standard paper input: 650-sheet

### TAILORED SOLUTIONS TO MEET EVERY CHALLENGE



Canon's Digital Transformation Services (DTS), bring together our leading hardware and software into an integrated technology ecosystem, designed to support your transformation journey. This offering combines Managed Print Services and Workspace Collaboration solutions, to help you gain transparency and control over the entire document lifecycle.



# **TECHNICAL SPECIFICATIONS**

# i-SENSYS X 1800P Series

DRINTED ENGINE

Printing method

Print speed

i-SENSYS X 1861P

Single sided : Up to 61 ppm (A4)
Up to 100 ppm(A5-Landscape)
Double sided : Up to 50.9 ipm (A4)

i-SENSYS X 1871P:

Fischer's A 16/1P.
Single sided : Up to 71 ppm (A4)
Up to 115 ppm(A5-Landscape)
Double sided : Up to 58.7 ipm (A4)

Monochrome laser beam printing

Up to 1200 x 1200 dpi Print resolution Warm-up time

Print ready message shown: Approx. 2 seconds or less from power on

Mono: approx. 4.9 seconds First Page Out Time

Recommended Monthly

i-SENSYS X 1861P: 3,000-16,000 pages i-SENSYS X 1871P: 4,000-20,000 pages Print Volume i-SENSYS X 1861P: Max 420,000 pages' i-SENSYS X 1871P: Max 450,000 pages' Duty cycle

5 mm-top, bottom, left and right

Advanced printing features

Secure Print Print from USB memory key (JPEG/TIFF/PDF/XPS) Barcode Print<sup>2</sup> iOS: AirPrint, Canon PRINT Business app

Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app Microsoft Universal Print

550-sheet cassette x 4 (Paper Feeder PF-J1) 2,000-sheet cassette (Paper Deck Unit PD-H1)

550-sheet cassette 100-sheet multi-purpose tray

MEDIA HANDLING

Paper input (Standard)

Paper input (Option)

Maximum paper input

Paper output Media types

Media sizes

Media weights

Double sided printing

**GENERAL FEATURES** Power requirements

Power consumption

Noise level

i-SENSYS X 1861P:

Sound power<sup>3</sup>
Active: Simplex 70 dB or less
Duplex 71 dB or less
Standby: Inaudible<sup>9</sup>

Sound pressure<sup>3</sup> Active: 55 dB or less Standby: Inaudible<sup>9</sup>

Standby: Inaudible Sound pressure<sup>3</sup> Active: 56 dB or less Standby: Inaudible<sup>9</sup>

Dimensions (W x D x H)

Weight

Operating environment

Control panel

**Processor Speed** Memory

Storage

Fonts

Network Protocol

75-sheet envelope cassetts (Envelope Feeder EF-B1) 4 300-sheets

Multi-Purpose Tray: Plain paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Coated paper, Pre-punched, Letterhead, Post card, Envelope Cassette: Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Colour paper, Coated paper, Pre-punched, Letterhead

Cassette (Standard): A4, A5, A5 (Landscape), A6, B5, B6, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, Custom sizes: Min. 99 x 148 mm Max. 216.0 x 355.6 mm.

Multi-purpose trav:

Multi-purpose tray: A4, A5, A5 (Candscape), A6, B5, B6, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, Index. Envelope (COMIO, NoIO, Monarch, C5, DL),Custom sizes: Min. 76.2 x 127 mm Max. 216.0 x 355.6 mm

Cassette (Optional):

Cassette (Optional). A4, A5, A5 (Landscape), A6, B5, B6, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, Custom sizes: Min. 99 x 148 mm Max. 216.0 x 355.6 mm

Envelope Feeder (Optional): Envelope (COM10, No10, Monarch, C5, DL)

Cassette (standard and optional): 60 to 135 g/m² Envelope Feeder (Optional): 80 to 100 g/m² Multi-purpose tray: 60 to 199 g/m²

Automatic
Cassette:
A4, A5, B5, Legal, Letter, Executive, OFFICIO,
B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL,
Foolscap, F4A, 16K
Custom size - Min. 148 x 210 mm
Max. 216 x 355.6 mm
60 to 120 g/m²

220-240V (±10%) 50/60Hz (±2Hz)

Asimum: Approx. 1500W or less
Active: Approx. 17.1.49W or less
Active: Approx. 17.1.49W or less
Standby: Approx. 1.3.69W or less
Sleep: Approx. 1.0W or less
Typical Electricity Consumption (TEC):
1861P = 0.61kWh/week<sup>8</sup>
1871P = 0.73kWh/week<sup>8</sup>
For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For\_Work/Lot26/index.aspx

i-SENSYS X 1871P Sound power<sup>3</sup> Active: 72 dB or less

430 mm x 465 mm x 370 mm

Approx. 20 kg

Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation)

5 Line LCD, 5 LED (Online, Ready, Message, Job and Energy saver), Buttons, 10-key numeric keypad

CONTROLLER 1.6GHz x 2

2GB

32GB eMMC (available space 15GB) UFRII (Ultra Fast Rendering), PCL5e<sup>4</sup>, PCL6, Adobe<sup>®</sup> PostScript3 **Printer Languages** 

93 PCL fonts (93 Roman, 10 Bitmap fonts, 2 OCR fonts) Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese)\*5

Barcode Fonts 136 PostScript fonts

Interface and connectivity

USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection

Direct Connection

Print: TCP/IP (LPD/Port9100/IPP/IPPS/FTP/WSD)

Management: SNMPv1, SNMPv3 (IPv4,IPv6)

Security: TLS1.3, IPSec, IP/Mac address filtering,
IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS), Dual

Network Support

Security (wireless):
Infrastructure Mode:
WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES), WPA3-SAE (AES), WPA-EAP (AES),
WPA2-EAP (AES), WPA3-EAP (AES)

Access Point Mode:
WPA2-PSK(AES)
Wi-Fi Direct Mode:
WPA2-PSK (AES)

Remote User Interface (RUI).

Software and Printer Management

Remote User Interface (RUI), Department ID Management, Toner Status Tool, iW Enterprise Management Console: Server-based

software for centralised management of a fleet of

eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics.

Content Delivery System: Server platform enables automatic firmware update to the device. uniFLOW online / uniFLOW online Express /

uniFLOW compatibility

Windows\* 11 / Windows\* 10 / Windows\* 8.1 / Server\* 2022 / Server\* 2019 / Server\* 2016 / Server\* 2012R2 / Server\* 2012 / Mac OS X version 10.12 & up Linux\* Operating Systems Compatibility

CONSUMABLES

All-in-One cartridges

TONER T15 Black (42,000 pages<sup>7</sup>)

ACCESSORIES/ OPTIONS

Items

Paper Feeder PF-J1 (550-sheet cassette) x 4 Paper Deck Unit PD-H1 (2,000-sheet cassette deck) Envelope Feeder EF-B1 (Envelope feeder cassette) Barcode Printing Kit-D1 (Enables barcode printing

capability)
PCL Font Set-Al (Enables Unicode printing capability on SAP and supports Andale font)
MiCard Multi (Card reader for identification with RFID or magnetic cards with uniFLOW)
Micard Plus (Card reader for identification with RFID or magnetic cards with uniFLOW)

Notes:

Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product

Accessory - Barcode Printing Kit-DI - is required

Declared noise emission in accordance with ISO 9296

[9] Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779



# **Software & Solutions**







### Compatibility









Canon Ireland 3006 Lake Drive

Citywest, Saggart Co. Dublin, Ireland Telephone No: 01 2052400

Facsimile No: 01 2052525 canon.ie

The Bower 4 Roundwood Avenue Stockley Park

Uxbridge

Canon (UK) Ltd

UB111AF

Canon Inc. canon.com Canon Europe

canon-europe.com

English edition © Canon Europa N.V.,2022

